

Steri-7 Limited

Version No: 1.2

Safety Data Sheet according to WHS and ADG requirements

Chemwatch Hazard Alert Code: 3

Issue Date: 05/11/2019 Print Date: 05/11/2019 L.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	Steri 7 Xtra Concentrate	
Synonyms	Not Available	
Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	
Other means of identification	Not Available	

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses		PC8: Biocidal products (e.g. Disinfectants, pest control).

Details of the supplier of the safety data sheet

Registered company name	Steri-7 Limited	
Address	20/8 Tilley Lane, Frenchs Forest NSW 2086	
Telephone	(02) 8209 3846	
Email	Email info@steri-7.com.au	

Emergency telephone number

Association / Organisation Steri-7 Limited	
Emergency telephone numbers	(02) 8209 3846 (office hours only)

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

 ${\sf HAZARDOUS\ CHEMICAL.\ DANGEROUS\ GOODS.\ According\ to\ the\ WHS\ Regulations\ and\ the\ ADG\ Code.}$

CHEMWATCH HAZARD RATINGS

	Min	Max	
Flammability	1		
Toxicity	1	1	0 = Minimum
Body Contact	2		1 = Low 2 = Moderate
Reactivity	0		3 = High
Chronic	3		4 = Extreme

Poisons Schedule Not Applicable		
Classification ^[1]	Classification ^[1] Eye Irritation Category 2A, Flammable Liquid Category 4, Skin Corrosion/Irritation Category 2	
Legend: 1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008		

Label elements

Hazard pictogram(s)	
SIGNAL WORD	WARNING

Hazard statement(s)

H319	Causes serious eye irritation.	
H227 Combustible liquid.		
H315	Causes skin irritation.	

Precautionary statement(s) General

P101	If medical advice is needed, have product container or label at hand.	
P102 Keep out of reach of children.		
P103	Read label before use.	

Precautionary statement(s) Prevention

P210 Keep away from heat/sparks/open flames/hot surfaces No smoking.	
P280 Wear protective gloves/protective clothing/eye protection/face protection.	

Precautionary statement(s) Response

P321	Specific treatment (see advice on this label).	
P362	Take off contaminated clothing and wash before reuse.	
P370+P378	In case of fire: Use alcohol resistant foam or normal protein foam for extinction.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P337+P313	If eye irritation persists: Get medical advice/attention.	
P302+P352 IF ON SKIN: Wash with plenty of water.		
P332+P313	If skin irritation occurs: Get medical advice/attention.	

Precautionary statement(s) Storage

P403+P235 Store in a well-ventilated place. Keep cool.

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
67-63-0	<10	isopropanol
27083-27-8	<10	poly(hexamethylenebiguanide hydrochloride)
71-36-3	<1	n-butanol
108-21-4	<1	isopropyl acetate
67-64-1	<1	acetone
541-02-6	<1	decamethylcyclopentasiloxane
64-17-5	<1	ethanol

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	 If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	 If skin irritation occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice. For advice, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

To treat poisoning by the higher aliphatic alcohols (up to C7):

- Gastric lavage with copious amounts of water.
- It may be beneficial to instill 60 ml of mineral oil into the stomach.
- Oxygen and artificial respiration as needed.
- Electrolyte balance: it may be useful to start 500 ml. M/6 sodium bicarbonate intravenously but maintain a cautious and conservative attitude toward electrolyte replacement unless shock or severe acidosis threatens.
- ▶ To protect the liver, maintain carbohydrate intake by intravenous infusions of glucose.
- + Haemodialysis if coma is deep and persistent. [GOSSELIN, SMITH HODGE: Clinical Toxicology of Commercial Products, Ed 5)

BASIC TREATMENT

- Establish a patent airway with suction where necessary.
- Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- Monitor and treat, where necessary, for shock.
- Monitor and treat, where necessary, for pulmonary oedema.
- Anticipate and treat, where necessary, for seizures.
- DO NOT use emetics. Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.
- Give activated charcoal.

ADVANCED TREATMENT

- Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- Positive-pressure ventilation using a bag-valve mask might be of use
- Monitor and treat, where necessary, for arrhythmias.
- Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- If the patient is hypoglycaemic (decreased or loss of consciousness, tachycardia, pallor, dilated pupils, diaphoresis and/or dextrose strip or glucometer readings below 50 mg), give 50% dextrose.
- Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- Treat seizures with diazepam.
- Proparacaine hydrochloride should be used to assist eye irrigation.

EMERGENCY DEPARTMENT

- Laboratory analysis of complete blood count, serum electrolytes, BUN, creatinine, glucose, urinalysis, baseline for serum aminotransferases (ALT and AST), calcium, phosphorus and magnesium, may assist in establishing a treatment regime. Other useful analyses include anion and osmolar gaps, arterial blood gases (ABGs), chest radiographs and electrocardiograph.
- Positive end-expiratory pressure (PEEP)-assisted ventilation may be required for acute parenchymal injury or adult respiratory distress syndrome.
- Acidosis may respond to hyperventilation and bicarbonate therapy.
- ► Haemodialysis might be considered in patients with severe intoxication.

Consult a toxicologist as necessary. BRONSTEIN, A.C. and CURRANCE, P.L. EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

For C8 alcohols and above.

Symptomatic and supportive therapy is advised in managing patients.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- Alcohol stable foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog Large fires only.

Special hazards arising from the substrate or mixture

Fire Incompatibility	Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
----------------------	--

Advice for firefighters

Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course. Use water delivered as a fine spray to control fire and cool adjacent area. Avoid spraying water onto liquid pools. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire.
Fire/Explosion Hazard	 Combustible. Slight fire hazard when exposed to heat or flame. Heating may cause expansion or decomposition leading to violent rupture of containers. On combustion, may emit toxic fumes of carbon monoxide (CO). May emit acrid smoke. Mists containing combustible materials may be explosive. Combustion products include: carbon dioxide (CO2) other pyrolysis products typical of burning organic material.
HAZCHEM	•3Z

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Environmental hazard - contain spillage. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite. Wipe up. Place in a suitable, labelled container for waste disposal. 					
	Environmental hazard - contain spill Chemical Class: alcohols and glyco For release onto land: recommende	ls		sted in ord	der of priority.	
	SORBENT TYPE RANK APPLICATIO	ON	COLLE		LIMITATIONS	
	LAND SPILL - SMALL					
	cross-linked polymer - particulate	1	shovel	shovel	R, W, SS	
	cross-linked polymer - pillow	1	throw	pitchfork	R, DGC, RT	
	sorbent clay - particulate	2	shovel	shovel	R,I, P	
	wood fiber - pillow	3	throw	pitchfork	R, P, DGC, RT	
	treated wood fiber - pillow	3	throw	pitchfork		
	foamed glass - pillow	4	throw	, pichfork		
	LAND SPILL - MEDIUM		1			
	cross-linked polymer - particulate	1	blower	skiploade	er R,W, SS	
	polypropylene - particulate	2	blower	skiploade	er W, SS, DGC	
	sorbent clay - particulate	2	blower	skiploade	er R, I, W, P, DGC	
	polypropylene - mat	3	throw	skiploade	er DGC, RT	
Major Spills	expanded mineral - particulate	3	blower	skiploade	er R, I, W, P, DGC	
	polyurethane - mat	4	throw	skiploade	er DGC, RT	
	polyurethane - mat 4 throw skiploader DGC, RT Legend DGC: Not effective where ground cover is dense R R; Not reusable I: Not incirerable P: Effectiveness reduced when rainy RT:Not effective where terrain is rugged SS: Not for use within environmentally sensitive sites W: Effectiveness reduced when windy Reference: Sorbents for Liquid Hazardous Substance Cleanup and Control; R.W Melvold et al: Pollution Technology Review No. 150: Noyes Data Corporation 1988 Moderate hazard. • Clear area of personnel and move upwind. • Alert Fire Brigade and tell them location and nature of hazard. • Wear breathing apparatus plus protective gloves. • Prevent, by any means available, spillage from entering drains or water course. • No smoking, naked lights or ignition sources. • Increase ventilation. • Stop leak if safe to do so. • Collect soild residues and seal in labelled containers for recycling. • Absorb remaining product with sand, earth or vermiculite. • Collect soild residues and seal in labelled drums for disposal. • Wash area and prevent runoff into drains. • Mash area and prevent runof drains or watereage services.					

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. Avoid smoking, naked lights or ignition sources. Avoid contact with incompatible materials.
---------------	---

	 When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions. DO NOT allow clothing wet with material to stay in contact with skin
Other information	 Store in original containers. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities

Suitable container	 Metal can or drum Packaging as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.
Storage incompatibility	 Alcohols are incompatible with strong acids, acid chlorides, acid anhydrides, oxidising and reducing agents. reacts, possibly violently, with alkaline metals and alkaline earth metals to produce hydrogen react with strong acids, strong caustics, aliphatic amines, isocyanates, acetaldehyde, benzoyl peroxide, chromic acid, chromium oxide, dialkylzincs, dichlorine oxide, ethylene oxide, hypochlorous acid, isopropyl chlorocarbonate, lithium tetrahydroaluminate, nitrogen dioxide, pentafluoroguanidine, phosphorus halides, phosphorus pentasulfide, tangerine oil, triethylaluminium, triisobutylaluminium should not be heated above 49 deg. C. when in contact with aluminium equipment

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	isopropanol	Isopropyl alcohol	400 ppm / 983 mg/m3	1230 mg/m3 / 500 ppm	Not Available	Not Available
Australia Exposure Standards	n-butanol	n-Butyl alcohol	Not Available	Not Available	50 ppm / 152 mg/m3	Not Available
Australia Exposure Standards	isopropyl acetate	Isopropyl acetate	250 ppm / 1040 mg/m3	1290 mg/m3 / 310 ppm	Not Available	Not Available
Australia Exposure Standards	acetone	Acetone	500 ppm / 1185 mg/m3	2375 mg/m3 / 1000 ppm	Not Available	Not Available
Australia Exposure Standards	ethanol	Ethyl alcohol	1000 ppm / 1880 mg/m3	Not Available	Not Available	Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1		TEEL-2	TEEL-3	
isopropanol	Isopropyl alcohol	400 ppm		2000 ppm	12000 ppm	
n-butanol	Butyl alcohol, n-; (n-Butanol)	60 ppm		800 ppm	8000 ppm	
isopropyl acetate	Isopropyl acetate	200 ppm		2700 ppm	16000 ppm	
acetone	Acetone	Not Available	9	Not Available	Not Available	
decamethylcyclopentasiloxane	Decamethylcyclopentasiloxane	4.8 ppm		53 ppm	320 ppm	
ethanol	Ethyl alcohol; (Ethanol) Not Availab		9	Not Available	15000 ppm	
Ingredient	Original IDLH		Revised IDL	н		
isopropanol	2,000 ppm		Not Available	Not Available		
poly(hexamethylenebiguanide hydrochloride)	Not Available		Not Available			
n-butanol	1,400 ppm	1,400 ppm		Not Available		
isopropyl acetate	1,800 ppm		Not Available			
acetone	2,500 ppm		Not Available			
decamethylcyclopentasiloxane	Not Available		Not Available			
ethanol	3,300 ppm		Not Available			

OCCUPATIONAL EXPOSURE BANDING

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit				
poly(hexamethylenebiguanide hydrochloride)	E	≤ 0.01 mg/m³				
decamethylcyclopentasiloxane	E	≤ 0.1 ppm				
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.					

For ethanol:

Odour Threshold Value: 49-716 ppm (detection), 101 ppm (recognition)

Eye and respiratory tract irritation do not appear to occur at exposure levels of less than 5000 ppm and the TLV-TWA is thought to provide an adequate margin of safety against such effects. Experiments in man show that inhalation of 1000 ppm caused slight symptoms of poisoning and 5000 ppm caused strong stupor and morbid sleepiness. Subjects exposed to 5000 ppm to 10000 ppm experienced smarting of the eyes and nose and coughing. Symptoms disappeared within minutes. Inhalation also causes local irritating effects to the eyes and upper respiratory tract, headaches, sensation of heat intraocular tension, stupor, fatigue and a need to sleep. At 15000 ppm there was continuous lachrymation and coughing.

For isopropyl acetate:

Odour Threshold Value: 0.50-34 ppm (detection), 0.91-41 ppm (recognition)

The TLV-TWA is thought to be protective against ocular and upper respiratory tract irritation. It must be noted however that one study demonstrated that the majority of subjects exposed at 200 ppm for 15 minutes experienced eye irritation.

Odour Safety Factor(OSF) OSF=74 (ISOPROPYL ACETATE)

Odour Threshold Value: 3.6 ppm (detection), 699 ppm (recognition)

Saturation vapour concentration: 237000 ppm @ 20 C

NOTE: Detector tubes measuring in excess of 40 ppm, are available.

Exposure at or below the recommended TLV-TWA is thought to protect the worker against mild irritation associated with brief exposures and the bioaccumulation, chronic irritation of the respiratory tract and headaches associated with long-term acetone exposures. The NIOSH REL-TWA is substantially lower and has taken into account slight irritation experienced by volunteer subjects at 300 ppm. Mild irritation to acclimatised workers begins at about 750 ppm - unacclimatised subjects will experience irritation at about 350-500 ppm but acclimatisation can occur rapidly. Disagreement between the peak bodies is based largely on the view by ACGIH that widespread use of acetone, without evidence of significant adverse health effects at higher concentrations, allows acceptance of a higher limit.

Half-life of acetone in blood is 3 hours which means that no adjustment for shift-length has to be made with reference to the standard 8 hour/day, 40 hours per week because body clearance occurs within any shift with low potential for accumulation.

A STEL has been established to prevent excursions of acetone vapours that could cause depression of the central nervous system.

Odour Safety Factor(OSF) OSF=38 (ACETONE)

Odour Threshold Value: 3.3 ppm (detection), 7.6 ppm (recognition)

Exposure at or below the recommended isopropanol TLV-TWA and STEL is thought to minimise the potential for inducing narcotic effects or significant irritation of the eyes or upper respiratory tract. It is believed, in the absence of hard evidence, that this limit also provides protection against the development of chronic health effects. The limit is intermediate to that set for ethanol, which is less toxic, and n-propyl alcohol, which is more toxic, than isopropanol

For n-butanol:

Odour Threshold Value: 0.12-3.4 ppm (detection), 1.0-3.5 ppm (recognition)

NOTE: Detector tubes for n-butanol, measuring in excess of 5 ppm are commercially available.

Exposure at or below the TLV-TWA is thought to provide protection against hearing loss due to vestibular and auditory nerve damage in younger workers and to protect against the significant risk of headache and irritation.

25 ppm may produce mild irritation of the respiratory tract 50 ppm may produce headache and vertigo.

Higher concentrations may produce marked irritation, sore throat, coughing, nausea, shortness of breath, pulmonary injury and central nervous system depression characterised by headache, dizziness, dullness and drowsiness.

6000 ppm may produce giddiness, prostration, narcosis, ataxia, and death.

Odour Safety Factor (OSF) OSF=60 (n-BUTANOL)

Exposure controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard 'physically' away from the worker and ventilation that strategically 'adds' and 'removes' air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in specific circumstances. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas.
 Safety glasses with side shields. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]
See Hand protection below
 Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended. It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times. Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers'

Steri 7 Xtra Concentrate	

	 technical data should always be taken into account to ensure selection of the most appropriate glove for the task. Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example: Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of. Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.
Body protection	See Other protection below
Other protection	 Barrier cream. Skin cleansing cream. Eye wash unit for bulk usage.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Clear colourless liquid		
Physical state	Liquid	Relative density (Water = 1)	0.95 - 1.05
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	6.0 - 8.0	Decomposition temperature	Not Available
Melting point / freezing point (°C)	0	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	100	Molecular weight (g/mol)	Not Available
Flash point (°C)	60 - 93	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Flammable.	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	25

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	The material is not thought to produce either adverse health effects or irritation of the respiratory tract following inhalation (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	Accidental ingestion of the material may be damaging to the health of the individual. Effects on the nervous system characterise over-exposure to higher aliphatic alcohols. These include headache, muscle weakness, giddiness, ataxia, (loss of muscle coordination), confusion, delirium and coma. Gastrointestinal effects may include nausea, vomiting and diarrhoea. In the absence of effective treatment, respiratory arrest is the most common cause of death in animals acutely poisoned by the higher alcohols. Aspiration of liquid alcohols produces an especially toxic response as they are able to penetrate deeply in the lung where they are absorbed and may produce pulmonary injury. Those possessing lower viscosity elicit a greater response. The result is a high blood level and prompt death at doses otherwise tolerated by ingestion without aspiration. In general the secondary alcohols are less toxic than the corresponding primary

Chronic Steri 7 Xtra Concentrate isopropanol
Chronic Steri 7 Xtra Concentrate
Chronic
Chronic
Chronic
Chronic
Lye
Цуе
Eye
Skin Contact

	TOXICITY	IRR	ITATION
	Dermal (rabbit) LD50: 3400 mg/kg ^[2]	Eye	(human): 50 ppm - irritant
	Inhalation (rat) LC50: 24 mg/l/4H ^[2]	Eye	e (rabbit): 1.6 mg-SEVERE
n-butanol	Oral (rat) LD50: 790 mg/kg ^[2]	Eye	e (rabbit): 24 mg/24h-SEVERE
		Eye	: adverse effect observed (irreversible damage) ^[1]
			n (rabbit): 405 mg/24h-moderate
		Skir	n: adverse effect observed (irritating) ^[1]
	TOXICITY		IRRITATION
	Dermal (rabbit) LD50: >17360 mg/kg ^[2]		Eye (human): 200 ppm/15m
	Inhalation (rat) LC50: 101.2 mg/l/8hm ^[2]		Eye (rabbit): 500 mg open
isopropyl acetate	Oral (rat) LD50: =6750 mg/kg ^[2]		Eye (rabbit): 500 mg/24h - mild
			Eye: no adverse effect observed (not irritating) ^[1]
			Skin (rabbit): 500 mg/24h - mild
			Skin: no adverse effect observed (not irritating) ^[1]
	ΤΟΧΙΟΙΤΥ		IRRITATION
			Eye (human): 500 ppm - irritant
	Inhalation (rat) LC50: 100.2 mg/l/8hr ^[2]		Eye (rabbit): 20mg/24hr -moderate
	Oral (rat) LD50: 1800-7300 mg/kg ^[2]		Eye (rabbit): 3.95 mg - SEVERE
acetone			Eye: adverse effect observed (irritating) ^[1]
			Skin (rabbit): 500 mg/24hr - mild
			Skin (rabbit):395mg (open) - mild
			Skin: no adverse effect observed (not irritating) ^[1]
	ΤΟΧΙΟΙΤΥ		IRRITATION
	Dermal (rabbit) LD50: >15248 mg/kg ^[2]		Eye (rabbit): 500 mg/24h - mild
	Inhalation (rat) LC50: 8.67 mg/l/4h ^[2]		Eye: no adverse effect observed (not irritating) ^[1]
decamethylcyclopentasiloxane	Oral (rat) LD50: >5000 mg/kg ^[1]		Skin (rabbit): 500 mg/24h - mild
			Skin: adverse effect observed (irritating) ^[1]
			Skin: no adverse effect observed (intraining) ^[1]
	TOXICITY		IRRITATION
	Inhalation (rat) LC50: 124.7 mg/l/4H ^[2]		Eye (rabbit): 500 mg SEVERE
	Oral (rat) LD50: =1501 mg/kg ^[2]		Eye (rabbit): 000 mg 32 vErkE
ethanol			Eye: adverse effect observed (irritating) ^[1]
othanor			Skin (rabbit):20 mg/24hr-moderate
			Skin (rabbit):400 mg (open)-mild
			Skin: no adverse effect observed (not irritating) ^[1]
Legend:			Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise
	specified data extracted from RTECS - Register of	IOXIC Effect o	r cnemical Substances

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	×	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×
		Legend: X – Data either not	available or does not fill the criteria for classification

yond. 🔰

Data either not available or does not fill the criteria for classification
 Data available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Steri	7	Xtra	Concentrate
-------	---	------	-------------

Steri 7 Xtra Concentrate	ENDPOINT TEST DURATION (HR)		S	PECIES	VALUE		SOURCE	
	Not Available Not Available			N	Not Available Not Avai		lable	Not Available
	ENDPOINT	ENDPOINT TEST DURATION (HR)		SPECIES	SPECIES		VALUE	SOURCE
	LC50	96		Fish			9-640mg/L	2
	EC50	48		Crustacea			12500mg/L	5
isopropanol	EC50	96		Algae or other aquatic plants			993.232mg/L	3
	EC0	24		Crustacea			5-102mg/L	2
	NOEC	5760		Fish			0.02mg/L	4
							g/-	
	ENDPOINT	TEST DU	RATION (HR)		SPECIES	VALUE		SOURCE
ly(hexamethylenebiguanide hydrochloride)	LC50	96			Fish	0.0254	5mg/L	4
	EC50	48			Crustacea	0.18mg	/L	4
	ENDPOINT	TEST DURAT	ION (HR)	SPECIES	6		VALUE	SOURCE
	LC50	96		Fish			1-376mg/L	2
	EC50	48		Crustace	а		1-328mg/L	2
n-butanol	EC50	96		Algae or	other aquatic plant	s	225mg/L	2
	BCF	24		Fish			921mg/L	4
	EC0	48		Crustacea			1-260mg/L	2
	NOEC	504		Crustace	а		4.1mg/L	2
	ENDPOINT	TEST DURATION (HR)		SPECIES		VALUE	SOURCE	
	LC50	96		Fish			37.529mg/L	3
isopropyl acetate	EC50	48		Crustacea		110mg/L	2	
	EC50	96		Algae or o	other aquatic plants	6	2.910mg/L	3
	NOEC	72		Algae or o	other aquatic plants	3	95mg/L	2
	ENDPOINT	TEST DURAT	ION (HR)	SPECIES			VALUE	SOURCE
	LC50	96		Fish			5-540mg/L	2
acetone	EC50	48		Crustacea			>100mg/L	4
accione	EC50	96			ther aquatic plants		20.565mg/L	4
	NOEC	240		Crustacea		1-866mg/L	2	
	ENDPOINT	TEST DURATI	ON (HR)	SPECIES			VALUE	SOURCE
	LC50	96		Fish			>0.016mg/L	2
amethylcyclopentasiloxane	EC50	48		Crustacea	Crustacea		>0.0029mg/L	2
	EC50	96		Algae or other aquatic plants			>0.012mg/L	2
	NOEC	48		Crustacea	Crustacea		>=0.0029mg/L	2
	ENDPOINT	TEST DURATI		SPECIES			VALUE	SOURCE
	LC50	96						2
-theory I				Fish			11-mg/L	
ethanol	EC50	48		Crustacea			2mg/L	4
	EC50	96		-	her aquatic plants		17.921mg/L	4
	NOEC	2016		Fish			0.000375mg/L	4
Legend:								Toxicity 3. EPIWIN

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
isopropanol	LOW (Half-life = 14 days)	LOW (Half-life = 3 days)
n-butanol	LOW (Half-life = 54 days)	LOW (Half-life = 3.65 days)
isopropyl acetate	LOW	LOW
acetone	LOW (Half-life = 14 days)	MEDIUM (Half-life = 116.25 days)

decamethylcyclopentasiloxane	HIGH	HIGH
ethanol	LOW (Half-life = 2.17 days)	LOW (Half-life = 5.08 days)

Bioaccumulative potential

Ingredient	Bioaccumulation
isopropanol	LOW (LogKOW = 0.05)
n-butanol	LOW (BCF = 0.64)
isopropyl acetate	LOW (BCF = 1.8)
acetone	LOW (BCF = 0.69)
decamethylcyclopentasiloxane	HIGH (LogKOW = 5.2)
ethanol	LOW (LogKOW = -0.31)

Mobility in soil

Ingredient	Mobility		
isopropanol	IIGH (KOC = 1.06)		
n-butanol	/EDIUM (KOC = 2.443)		
isopropyl acetate	OW (KOC = 9.479)		
acetone	HIGH (KOC = 1.981)		
decamethylcyclopentasiloxane	LOW (KOC = 145200)		
ethanol	HIGH (KOC = 1)		

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

	 Containers may still present a chemical hazard/ danger when empty. Return to supplier for reuse/ recycling if possible. Otherwise: If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. Where possible retain label warnings and SDS and observe all notices pertaining to the product. Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. A Hierarchy of Controls seems to be common - the user should investigate: Reduction Reuse
Product / Packaging disposal	 Recycling Disposal (if all else fails) This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate. DO NOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority. Recycle wherever possible, or dispose of in an authorised landfill.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	NO
HAZCHEM	•3Z

Land transport (ADG)

UN number	3082		
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.		
Transport hazard class(es)	Class 9 Subrisk Not Applicable		
Packing group	III		
Environmental hazard	Not Applicable		

Environmentally Hazardous Substances meeting the descriptions of UN 3077 or UN 3082 are not subject to this Code when transported by road or rail in; (a) packagings; (b) IBCs; or

(c) any other receptacle not exceeding 500 kg(L).

- Australian Special Provisions (SP AU01) - ADG Code 7th Ed.

Air transport (ICAO-IATA / DGR)

3082			
Environmentally hazardous substance, liquid, n.o.s. *			
ICAO/IATA Class			
ERG Code	9L		
II			
Not Applicable			
Special provisions		A97 A158 A197	
Cargo Only Packing Instructions		964	
Cargo Only Maximum Qty / Pack		450 L	
Passenger and Cargo Packing Instructions		964	
Passenger and Cargo Maximum Qty / Pack		450 L	
Passenger and Cargo Limited Quantity Packing Instructions		Y964	
Passenger and Cargo Limited Maximum Qty / Pack		30 kg G	
	Environmentally hazardo ICAO/IATA Class ICAO / IATA Subrisk ERG Code III Not Applicable Special provisions Cargo Only Packing In Cargo Only Maximum Passenger and Cargo Passenger and Cargo	Environmentally hazardous substance, liquid, n.o.s. * ICAO/IATA Class 9 ICAO / IATA Subrisk Not Applicable ERG Code 9L III Not Applicable Special provisions Cargo Only Packing Instructions Cargo Only Maximum Qty / Pack Passenger and Cargo Maximum Qty / Pack Passenger and Cargo Limited Quantity Packing Instructions	Environmentally hazardous substance, liquid, n.o.s. * ICAO/IATA Class 9 ICAO / IATA Subrisk Not Applicable ERG Code 9L III Not Applicable Special provisions A97 A158 A197 Cargo Only Packing Instructions 964 Cargo Only Maximum Qty / Pack 450 L Passenger and Cargo Maximum Qty / Pack 450 L Passenger and Cargo Limited Quantity Packing Instructions 964

Sea transport (IMDG-Code / GGVSee)

UN number	3082		
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.		
Transport hazard class(es)	IMDG Class 9 IMDG Subrisk Not Applicable		
Packing group	III		
Environmental hazard	Not Applicable		
Special precautions for user	EMS NumberF-A , S-FSpecial provisions274 335 969Limited Quantities5 L		

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

ISOPROPANOL IS FOUND ON THE FOLLOWING REGULATORY LISTS

- Australia Dangerous Goods Code (ADG Code) Dangerous Goods List Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes Australia Exposure Standards
- Australia Exposure Standards
- Australia Hazardous Chemical Information System (HCIS) Hazardous Chemicals Australia Inventory of Chemical Substances (AICS)
- GESAMP/EHS Composite List GESAMP Hazard Profiles
- IMO IBC Code Chapter 17: Summary of minimum requirements

IMO IBC Code Chapter 18: List of products to which the Code does not apply

IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances IMO Provisional Categorization of Liquid Substances - List 2: Pollutant only mixtures containing at least 99% by weight of components already assessed by IMO IMO Provisional Categorization of Liquid Substances - List 3: (Trade-named) mixtures containing at least 99% by weight of components already assessed by IMO, presenting safety hazards International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs International Air Transport Association (IATA) Dangerous Goods Regulations International Maritime Dangerous Goods Requirements (IMDG Code) United Nations Recommendations on the Transport of Dangerous Goods Model Regulations

POLY(HEXAMETHYLENEBIGUANIDE HYDROCHLORIDE) IS FOUND ON THE FOLLOWING REGULATORY LISTS

 Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List
 Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6

 Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals
 International Air Transport Association (IATA) Dangerous Goods Regulations

 Australia Inventory of Chemical Substances (AICS)
 International Maritime Dangerous Goods Requirements (IMDG Code)

International Maritime Dangerous Goods Requirements (IMDG Code) United Nations Recommendations on the Transport of Dangerous Goods Model Regulations

N-BUTANOL IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes Australia Exposure Standards

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals Australia Inventory of Chemical Substances (AICS)

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6

GESAMP/EHS Composite List - GESAMP Hazard Profiles

ISOPROPYL ACETATE IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes Australia Exposure Standards

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals Australia Inventory of Chemical Substances (AICS)

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix B (Part 3)

GESAMP/EHS Composite List - GESAMP Hazard Profiles

ACETONE IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes

Australia Exposure Standards Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australia Inventory of Chemical Substances (AICS)

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5 $\,$

GESAMP/EHS Composite List - GESAMP Hazard Profiles

DECAMETHYLCYCLOPENTASILOXANE IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)

ETHANOL IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List

Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes Australia Exposure Standards

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals Australia Inventory of Chemical Substances (AICS)

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -Appendix B (Part 3)

GESAMP/EHS Composite List - GESAMP Hazard Profiles

IMO IBC Code Chapter 17: Summary of minimum requirements

IMO IBC Code Chapter 17: Summary of minimum requirements IMO IBC Code Chapter 18: List of products to which the Code does not apply IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances IMO Provisional Categorization of Liquid Substances - List 1: Pure or technically pure products

International Air Transport Association (IATA) Dangerous Goods Regulations International Maritime Dangerous Goods Requirements (IMDG Code) United Nations Recommendations on the Transport of Dangerous Goods Model Regulations

 IMO IBC Code Chapter 17: Summary of minimum requirements

 IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk

 IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances

 International Air Transport Association (IATA) Dangerous Goods Regulations

 International Maritime Dangerous Goods Requirements (IMDG Code)

 United Nations Recommendations on the Transport of Dangerous Goods Model

 Regulations

 IMO IBC Code Chapter 17: Summary of minimum requirements

 IMO IBC Code Chapter 18: List of products to which the Code does not apply

 IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances

 International Air Transport Association (IATA) Dangerous Goods Regulations

 International Maritime Dangerous Goods Requirements (IMDG Code)

 United Nations Recommendations on the Transport of Dangerous Goods Model

 Regulations

IMO IBC Code Chapter 18: List of products to which the Code does not apply IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances IMO Provisional Categorization of Liquid Substances - List 2: Pollutant only mixtures containing at least 99% by weight of components already assessed by IMO IMO Provisional Categorization of Liquid Substances - List 3: (Trade-named) mixtures containing at least 99% by weight of components already assessed by IMO, presenting safety hazards

International Air Transport Association (IATA) Dangerous Goods Regulations International Maritime Dangerous Goods Requirements (IMDG Code) United Nations Recommendations on the Transport of Dangerous Goods Model Regulations

National Inventory Status

National Inventory	Status		
Australia - AICS	Yes		
Canada - DSL	Yes		
Canada - NDSL	No (n-butanol; decamethylcyclopentasiloxane; poly(hexamethylenebiguanide hydrochloride); acetone; ethanol; isopropyl acetate; isopropanol)		
China - IECSC	Yes		
Europe - EINEC / ELINCS / NLP	No (poly(hexamethylenebiguanide hydrochloride))		
Japan - ENCS	Yes		
Korea - KECI	Yes		
New Zealand - NZIoC	Yes		
Philippines - PICCS	Yes		
USA - TSCA	Yes		
Taiwan - TCSI	Yes		
Mexico - INSQ	Yes		
Vietnam - NCI	Yes		
Russia - ARIPS	Yes		
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)		

SECTION 16 OTHER INFORMATION

Revision Date	05/11/2019
Initial Date	05/11/2019

Version	Issue Date	Sections Updated
0.2.1.1.1	05/11/2019	Acute Health (eye), Chronic Health, Classification, Engineering Control, First Aid (eye), Personal Protection (hands/feet)

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chernwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC – TWA: Permissible Concentration-Time Weighted Average PC – STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit。 IDLH: Immediately Dangerous to Life or Health Concentrations OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

Powered by AuthorITe, from Chemwatch.