

Label

POI SON

**KEEP OUT OF REACH OF CHILDREN
READ SAFETY DIRECTIONS BEFORE OPENING OR USING**

BI FORCE® 100SC WATER-BASED Termiticide & Insecticide

ACTIVE CONSTITUENT: 100g/L BI FENTHRI N

GROUP	3A	INSECTICIDE
--------------	-----------	--------------------

**For pre-construction and post-construction
management of Subterranean Termites and for the control
of a range of other urban pests both indoors and outdoors as
specified in the Directions For Use.**

IMPORTANT:

**RESTRICTED CHEMICAL PRODUCT ONLY TO BE SUPPLIED TO,
OR USED BY AN AUTHORISED PERSON**

IMPORTANT:

READ THE ATTACHED LEAFLET BEFORE OPENING OR USING

CONTENTS: 1L, 5L, 10L, 20L, 200L

APVMA Approval No. 62837/0409



Sherwood Chemicals Australasia Pty Ltd
Level 3, 1060 Hay St
WEST PERTH 6005
AUSTRALIA
Tel: 08 9219 4683
Fax: 08 9219 4672

BIFORCE® is a registered Trademark™ of SHERWOOD CHEMICALS PUBLIC COMPANY LTD, THAILAND

CONDITIONS OF USE BY AUTHORIZED PERSONS

The Pest Control Operator must be licensed under state legislation.

For pre-construction termite treatments, the Pest Control Operator must notify site supervisor, if any, and workers who come into contact with uncovered treated soil prior to laying the moisture membrane, to wear appropriate personal protective equipment and to observe re-entry requirements. (For personal protective equipment, refer to "SAFETY DIRECTIONS", and for re-entry refer to "PRECAUTIONS RE-ENTRY PERIODS" below).

PRECAUTIONS AND RE-ENTRY PERIODS

DO NOT spray into the air or directly on humans, pets or animals. Avoid contact with food, food utensils or preparation surfaces.

Re-entry period

Pre-construction: Re-entry - **DO NOT** allow entry into uncovered treated areas until the spray has dried. When prior entry is necessary, wear cotton overalls buttoned to the neck, wrist and elbow-length PVC, neoprene or nitrile gloves and chemical resistant footwear. Clothing must be laundered after each day's use.

Post-Construction and urban pest control: Re-entry **DO NOT** allow people and pets to enter treated areas until the spray has dried. When prior entry is necessary, wear cotton overalls buttoned to the neck, wrist and elbow-length PVC, neoprene or nitrile gloves and chemical resistant footwear. Clothing must be laundered after each day's use.

STORAGE, STORAGE AND DISPOSAL

Store in closed original container, in a cool, well-ventilated area away from children, animals, food and feedstuffs. DO NOT store for prolonged periods in direct sunlight. In case of spillage, confine and absorb spilled product with absorbent material such as sand, clay or cat litter. Dispose of waste as indicated below or according to the Australian Standard AS 2507 – Storage and Handling of Pesticides. DO NOT allow spilled product to enter sewers, drains, creeks or any other waterways.

For REFILLABLE containers: Empty contents fully into application equipment. Close all valves and return to point of supply for refill or storage.

For 1 L, 5 L, 10L, 20 L Containers

Triple or preferably pressure rinse containers before disposal. Add rinsings to spray tank. DO NOT dispose of undiluted chemicals on-site. If recycling, replace cap and return clean containers to recycler or designated collection point. If not recycling, break, crush or puncture and bury empty containers in a local authority landfill. If no landfill is available, bury the containers below 500 mm in a disposal pit specifically marked and set up for this purpose clear of waterways, vegetation and tree roots. Empty containers and product should not be burnt. DO NOT bury waste or surplus product. Dispose of undiluted waste by either dilution and use according to the Directions for Use or returning to the point of purchase in the original container for controlled disposal. Dispose of diluted surplus product by using according to the Directions for Use. DO NOT re-use empty container.

Envirodrum (200L)

Store the original sealed Envirodrum in a cool well-ventilated area. DO NOT store for prolonged periods in direct sunlight. DO NOT tamper with the Micro Matic valve or the security seal. DO NOT contaminate the Envirodrum with water or any foreign matter. After each use of the product, please ensure that the Micro Matic coupler delivery system and hoses are disconnected, triple rinsed with clean water and drained accordingly. When the contents of the Envirodrum have been used, please return the Envirodrum to the point of purchase. The Envirodrum remains the property of Sherwood Chemicals.

SAFETY DIRECTIONS

Poisonous if swallowed. Will damage the eyes and will irritate the skin. Avoid contact with eyes and skin. DO NOT inhale vapour or spray. When opening the container and preparing spray, wear cotton overalls buttoned to the neck and wrist, a washable hat, elbow-length PVC, neoprene or nitrile gloves, face shield or goggles and chemical resistant footwear. When using prepared spray, wear cotton overalls buttoned to the neck and wrist, a washable hat, elbow-length PVC, neoprene or nitrile gloves, face shield or goggles and chemical resistant footwear. When using in enclosed areas, wear cotton overalls buttoned to the neck and wrist, a washable hat, elbow-length PVC, neoprene or nitrile gloves, face shield or goggles and chemical resistant footwear and half-face respirator with the combined dust and gas cartridge. If clothing becomes contaminated with product or wet with spray, remove clothing immediately. If product or spray on skin, immediately wash area with soap and water. If product in eyes, wash it out immediately with water. After use and before eating, drinking or smoking, wash hands, arms and face thoroughly with soap and water. Thoroughly ventilate treated areas before reoccupying. After each day's use, wash gloves, face shield or goggles, respirator (if rubber wash with detergent and warm water) and contaminated clothing.

FIRST AID

If poisoning occurs, contact a doctor or Poisons Information Centre on 131126. See additional information on the **Material Safety Data Sheet**.

MATERIAL SAFETY DATA SHEET.

Additional information is listed in the Material Safety Data Sheet (MSDS). A Material Safety Data Sheet for BIFORCE® 100SC WATER-BASED TERMITICIDE & INSECTICIDE is available from Sherwood on request. Call Customer Service on 0421 667 972

CONDITIONS OF SALE:

The use of BIFORCE® 100SC WATER-BASED TERMITICIDE & INSECTICIDE being beyond the control of the manufacturer, no warranty expressed or implied is given by Sherwood Chemicals., regarding its suitability, fitness or efficiency for any purpose for which it is used by the buyer, whether in accordance with the directions or not and Sherwood Chemicals accepts no responsibility for any consequence whatsoever resulting from the use of this product.

Batch No:

Date of Manufacture:

APVMA Approval No.:

**1L
5L
10L
20L
200L**

POI SON

KEEP OUT OF REACH OF CHILDREN
READ SAFETY DIRECTIONS BEFORE OPENING OR USING

BI FORCE® 100SC WATER-BASED Termiticide & Insecticide

ACTIVE CONSTITUENT: 100g/L BI FENTHRIN

GROUP 3A INSECTICIDE

For pre-construction and post-construction
management of Subterranean Termites and for the control
of a range of other urban pests as specified in the
Directions For Use.

IMPORTANT:
RESTRICTED CHEMICAL PRODUCT ONLY TO BE SUPPLIED TO,
OR USED BY AN AUTHORISED PERSON.

IMPORTANT:
READ THE LEAFLET BEFORE OPENING OR USING

Distributed by;



Sherwood Chemicals Australasia Pty Ltd
Level 3, 1060 Hay St
WEST PERTH 6005
AUSTRALIA
Tel: 08 9219 4683
Fax: 08 9219 4672

BI FORCE® is a registered Trademark™ of SHERWOOD CHEMICALS PUBLIC COMPANY LTD, THAILAND

DI RECTIONS FOR USE:

RESTRAI NTS:

DO NOT use this product at less than indicated label rates.

DO NOT apply to soils if excessively wet or immediately after heavy rain to avoid run-off of the chemical.

DO NOT use in cavity walls (except via certified cavity infill reticulation systems or direct treatment of nest).

PEST	SITUATI ON	STATE	RATE	CRI TI CAL COMMENTS
Spiders	Internal & external areas & surrounds of domestic, commercial, public & industrial buildings and structures	All States	25-50mL /10L	<p>Use the higher rate in situation where pest pressure is high, when rapid knockdown and/or maximum residual protection is desired. Pay particular attention to protected dark areas such as cracks and crevices, under floors, eaves and other known hiding or resting places. For overall band surface spray, apply as a coarse, low pressure surface spray to areas where spiders hide, frequent and rest. Spray to the point of run-off using around 5 L of spray mixtures per 100 m² and ensuring thorough coverage of the treated surfaces. For crack and crevice treatment use an appropriate solid stream nozzle. For maximum spider control use a two part treatment.</p> <ol style="list-style-type: none"> 1. Crack and crevice. 2. Overall band spray of surfaces.
Papernest Wasps	Internal & external areas & surrounds of domestic, commercial, public & industrial buildings and structures	All States	50mL/10L	<p>Apply prepared solution to the point of run-off directly to the papernest ensuring thorough and even coverage. When all adult wasps have been knocked-down the nest may be safely removed from the structure.</p>
Ants (excluding Red imported Fire Ants), cockroaches, mosquitoes, fleas, flies, ticks (excluding the paralysis tick <i>Ixodes holocyclus</i>) (Adults & Nymphs)	Internal & external area & surrounds of domestic, commercial, public & industrial buildings and structures	All States	50-100 mL/10 L	<p>Use the higher rate in situations where pest pressure is high, when rapid knockdown and/or maximum residual protection is desired. The lower rate may be used for follow-up treatments. On non-porous surfaces apply as a coarse spray at the rate of 1 L solution per 20 m². When treating non-porous surfaces do not exceed the point of run-off.</p> <p>On porous surfaces or use through power equipment, spray at the rate of 1 L of solution per 10 m². When treating porous surfaces do not exceed the point of run-off.</p> <p>Ants: To control ants apply to trails and nests. Repeat as necessary.</p> <p>Fleas and Ticks: To control fleas and ticks apply prepared solution to outside surfaces of buildings and surrounds including but not limited to foundations, verandahs, window frames, eaves, patios, garages, pet housing, soil, turf, trunks or woody ornamentals or other areas where pests congregate or have been seen.</p> <p>Flies and Mosquitoes: To control flies and mosquitoes apply prepared solution to surfaces where insects rest or harbour. Reapply as necessary.</p> <p>Perimeter treatments: Apply the prepared solution to a band of soil or vegetation two to three metres wide around and adjacent to the structure. Also treat the foundation of the structure to a height of approximately one metre. Use a spray volume of 5 to 10 L per 100 m². Higher volumes of water may be needed if organic matter is present or foliage is dense.</p>

PEST	SITUATION	STATE	RATE	Critical Comments
Subterranean Termites	Domestic, public, commercial & industrial areas	All States, except Tas	Refer to Table A	Refer to Table B

TABLE A: BI FORCE® 100SC WATER-BASED Termicide and Insecticide use rates for management of SUBTERRANEAN TERMITES

SITUATION	All areas SOUTH of the Tropic of Capricorn (except Tas)		All areas NORTH of the Tropic Capricorn	
	RATE	Expected Protection Period*	RATE	Expected Protection Period*
Pre-Construction Barriers Under slabs and under suspended floors with less than 400 mm crawl space	1L/100L	At least 10 years	1.5L/100 L	5 years
			1L/100 L **	4 years
	500mL/100 L	10 years	750mL/100 L **	3 years
			500mL/100 L **	2 years
Perimeter Barriers For new and existing buildings	1L/100L	At least 10 years	1.5L/100 L	5 years
	500mL/100 L	10 years	1L/100 L	4 years
	250mL/100 L	3 years	750mL/100 L	3 years
			500mL/100 L	2 years
Post-Construction Barriers Under slabs and under suspended floors with less than 400 mm crawl space	1L/100L	At least 10 years	1.5L/100 L	5 years
			1L/100 L	4 years
	500mL/100 L	10 years	750mL/100 L	3 years
			500mL/100 L	2 years
Reticulation Systems Perimeter and/or service penetration treatment only	1L/100 L	At least 10 years	1.5L/100 L	5 years
	500mL/100 L	10 years	1L/100 L	4 years
	250mL/100 L	3 years	750mL/100 L	3 years
			500mL/100 L	2 years
Reticulation Systems Cavity infill & footing barriers	500mL/100 L	5 years	1L/100 L	2 years
Protection of Poles & Fence Posts	500mL/100 L	10 years	1.5L/100 L	5 years
			1L/100 L	4 years
			750mL/100 L	3 years
Nest Eradication	500mL/100 L	Not applicable	500mL/100 L	Not applicable
* Several factors contribute to the estimated length of protection provided for each termite treatment. The actual protection period will depend on the termite hazard, climate, soil conditions and rate of termicide used. The need for retreatment is to be determined as a result of at least an annual inspection, or more frequently in high risk area, by a qualified licensed Pest Control Operator.				
** This rate must be used in conjunction with a <u>certified</u> reticulation system that is capable of distributing the Termicide & Insecticide solution according to the product label and the Australian Standard AS 3660 Series.				

TABLE B CRITICAL COMMENTS for use against SUBTERRANEAN TERMITES

SITUATION	CRITICAL COMMENTS
Pre-Construction Barriers Under slabs for protection of new buildings * , **	<ul style="list-style-type: none"> Apply with suitable application equipment to form a complete and continuous chemical barrier (both vertical and horizontal) under the slab. The formation of the barrier may require a combination of conventional open wand application and soil trenching and/or rodding applications. Recommended rod spacing should be between 150 and 300 mm, as per soil type. For additional information refer to "CRITICAL APPLICATION DETAILS" on this label and the Australian Standard AS 3660 Series.
Pre-Construction Barriers Under suspended floors * , **	<ul style="list-style-type: none"> For areas under suspended floors with restricted access (typically with less than 400mm clearance), the entire subfloor area should be treated as a continuous horizontal barrier, which completely abuts an internal vertical barrier (if necessary) around any substructure wall. Ideally, this operation should be done during construction of the building while access is more readily available. For areas beneath suspended floors which have adequate access (eg. more than 400 mm clearance), install perimeter barriers around each individual pier, stump, service penetration and substructure wall.
Perimeter Barriers For new and existing buildings **	<ul style="list-style-type: none"> Perimeter barriers (both horizontal and vertical, external and where required, internal and sub-floor) are an essential part of termite protection and must be installed at the completion of the building. Perimeter barriers should be installed around slabs, piers, substructure walls and external penetrations points. Apply with suitable application equipment to form a continuous chemical barrier (both vertical and horizontal) around the structure and to a depth reaching 80mm below the top of the footings, where appropriate. The formation of the barrier may require a combination of several application techniques, including soil trenching and/or rodding and open wand applications.
Post-Construction Barrier Treatments For the protection of existing buildings **	<ul style="list-style-type: none"> Apply with suitable application equipment to form a complete and continuous barrier (both horizontal & vertical) around and under the buildings and structures as in accordance with AS3660 with particular emphasis on any known infestations areas. To form the chemical barrier a number of application techniques may be needed including soil rodding; trenching; open wand and sub-slab injections. Chemical barriers beneath concrete will require drilling. Recommended drill hole spacing is between 150mm and 300mm. To enhance chemical distribution, use a lateral dispersion tip on the injector and deliver up to 10L of emulsion per linear meter. Drill holes should be no more than 150mm from foundation walls or expansion joints to ensure complete formation of a chemical barrier. For areas under suspended floors with restricted access (typically with less than 400mm clearance), the entire subfloor area should be treated as a continuous horizontal barrier, which completely abuts an internal vertical barrier (if necessary) around any substructure wall. Otherwise, install perimeter barriers around each individual pier, stump, penetration point and structure wall.
Reticulation Systems Perimeter and/or service penetration treatment only	<ul style="list-style-type: none"> BIFORCE® 100SC WATER-BASED TERMITICIDE & INSECTICIDE must be used through a certified reticulation system to form and replenish perimeter barriers around buildings and service penetrations. The system must be installed according to the manufacturer's specifications and be capable of distributing the termiticide emulsion according to the product label and the Australian Standard AS 3660 Series. Perimeter barriers consist of a horizontal barrier abutting a vertical barrier, which must reach down to the top of the footing. Delivery pipes must be placed in such a position to ensure that the requirements for both horizontal and vertical barriers as specified in the Australian Standard AS 3660 Series are met. Special attention must also be afforded to the positioning of the delivery pipes to ensure that the resultant termiticidal barriers are continuous and complete. Apply the prepared termiticide emulsion by pumping through the system according to the manufacturer's specifications. Use a minimum delivery volume of 100 L of emulsion per m³ of soil. This equates to a delivery volume of 5 L of emulsion per linear metre for a vertical barrier 300 mm x 150 mm in dimension. Pre-Construction – For use in conjunction with full soil treatment horizontal barriers only: Apply the diluted emulsion through the perimeter reticulation system as specified above. Follow instructions for Pre-Construction horizontal barrier formation.

Reticulation Systems Cavity infill & footing barriers	<ul style="list-style-type: none"> The system must be installed according to the manufacturer's specifications and be capable of distributing the termiticide solution according to the product label and the Australian Standard AS 3660 Series. Delivery pipes must be placed in such a position to ensure that the requirements for both horizontal and vertical barriers as specified in the Australian Standard AS 3660 Series are met. Special attention must also be afforded to the positioning of the delivery pipes to ensure that the resultant termiticidal barriers are continuous and complete. Apply the prepared termiticide solution by pumping through the system according to the manufacturer's specifications with delivery volume of 2L of solution per linear metre of delivery pipe. Note: where this system is to be installed at the pre-construction stage, a full under slab pre-construction barrier, applied by either open wand application or suitably certified reticulation system, is also recommended. The recommended rate of application is 2 L of solution per linear metre which equates to 2 L of solution per 0.0068 m³ or approximately 7 L of sand. Should the volume of fill in the wall cavity deviate from 7 L (0.17 m x 0.04 m x 1 m = 0.0068 m³) per linear metre of wall cavity, then the amount of BIFORCE® 100SC WATER-BASED TERMITICIDE & INSECTICIDE solution applied per linear metre of wall cavity should be adjusted accordingly. As a guide, the target bifenthrin loading of treated sand/soil in a cavity infill situation is 110 mg/kg South of the Tropic of Capricorn and 220 mg/kg North of the Tropic of Capricorn. To facilitate more even distribution of BIFORCE® 100SC WATER-BASED TERMITICIDE & INSECTICIDE solution in the wall cavity, ensure that the fill is evenly compacted at the time of installation. To further enhance distribution saturation of the sand/soil in the infill is recommended at the time of treatment.
Protection of Service Poles & Fence Posts	<ul style="list-style-type: none"> Create a continuous termiticide barrier 450 mm deep and 150 mm wide around the pole or post by soil injection or rodding. For new poles and posts, treat backfill and the bottom of the hole. Use 100 L of solution per m³ of soil. Regular inspections should be undertaken to determine when and if treatment is necessary. If disturbance of the barrier has occurred, retreatment of the area affected will be required. Posts and poles may also be drilled and injected with spray solution. Note: For existing poles and posts, it is impractical to treat the full depth and underneath of such poles and posts and therefore the possibility of future termite attack from below the treated area cannot be ruled out.
Eradication of Termite Nest	<ul style="list-style-type: none"> Locate nest and flood with insecticide solution. Trees, poles, posts and stumps containing nests may require drilling prior to treatment with termiticide solution. The purpose of drilling is to ensure the termiticide solution is distributed throughout the entire nest. Drill holes in live trees should be sealed with an appropriate caulking compound after injection.

Notes to Critical Comments

* An external perimeter barrier (both horizontal and vertical) is an essential part of termite protection and must be installed at the completion of the building. Refer to "Perimeter Barriers" in this LEAFLET, for further details

** Chemical barriers that have been disturbed by construction, excavation and/or landscaping activities will need to be reapplied to restore continuity of the barrier.

NOTE: The termiticide barrier provided by this product has a finite life. This together with the recommendation to undertake annual inspection must be stated on the durable notice required by the BCA, B1.3 (j) (ii).

NOT TO BE USED FOR ANY PURPOSE, OR IN ANY MANNER, CONTRARY TO THIS LABEL UNLESS AUTHORIZED UNDER APPROPRIATE LEGISLATION.

CONDITION OF USE BY AUTHORIZED PERSONS

The pest control operator must be licensed under state legislation. The pest operator must notify site supervisor, if any, and workers who come into contact with uncovered treated soil prior to laying the moisture membrane, to wear appropriate personal protective equipment and to observe re-entry requirements.(For personal protective equipment, refer to "SAFETY DIRECTIONS", and for re-entry, refer to "PRECAUTION: RE-ENTRY PERIODS", below).

GENERAL INSTRUCTIONS

Urban pest control-BIFORCE® 100SC WATER-BASED TERMITICIDE & INSECTICIDE is a powerful knockdown and residual pesticide. Ants, cockroaches, fleas, flies, mosquitoes, spiders, ticks and wasps are controlled by direct contact with spray and also by residual action as they come in to contact with treated surfaces.

Termites – The use of BIFORCE® 100SC WATER-BASED TERMITICIDE & INSECTICIDE will help prevent and control subterranean termite infestations in and around building and structures when used in accordance with the Australian Standard AS 3660 Series, Termite Management. A dilute termitecidal solution must be adequately dispersed into the soil to establish a barrier between the building and subterranean termites in the soil. The purpose of a termite barrier is to prevent concealed termite entry into the building. The biology and behaviour of the termite species involved should be considered by the pest control operator in determining which control measures are most appropriate to control and prevent termite infestations.

INSECTICIDE RESISTANCE WARNING

GROUP 3A INSECTICIDE For insecticide resistance management BIFORCE® 100SC WATER-BASED TERMITICIDE & INSECTICIDE is a Group 3A insecticide. Some naturally occurring insect biotypes resistant to BIFORCE® 100SC WATER-BASED TERMITICIDE & INSECTICIDE and other group 3A insecticide may exist through normal genetic variability in any insect population. The resistant individuals can eventually dominate the insect population if BIFORCE® 100SC WATER-BASED TERMITICIDE & INSECTICIDE or other group 3A insecticides are used repeatedly. The effectiveness of BIFORCE® 100SC WATER-BASED TERMITICIDE & INSECTICIDE on resistant individuals could be significantly reduced. Since occurrence of resistant individuals is difficult to detect prior to use, Sherwood Chemicals accepts no liability for any losses that may result from the failure of BIFORCE® 100SC WATER-BASED TERMITICIDE & INSECTICIDE to control resistant insects. BIFORCE® 100SC WATER-BASED TERMITICIDE & INSECTICIDE may be subject to specific resistance management strategies. For further information, contact your local supplier, SHERWOOD CHEMICALS representatives or local agricultural department agronomist.

MIXING

Add the required quantity BIFORCE® 100SC WATER-BASED TERMITICIDE & INSECTICIDE to water in the spray tank and mix thoroughly. Maintain agitation during both mixing and application. To facilitate even application of the termitecidal solution over the area to be treated, the addition of a marker dye at label rate is recommended. On hard to wet soil the penetration of the termitecidal solution may be improved by the addition of a soil surfactant at label rate.

Critical Application Details

The application of BIFORCE® 100SC WATER-BASED TERMITICIDE & INSECTICIDE to form both horizontal and vertical chemical barriers must be in accordance with the Australian Standard AS 3660 Series. For treatment of new and existing buildings, both horizontal and vertical barriers may be required, around and under the building. External perimeter barriers and where required, internal perimeter barriers, are an essential part of this treatment. The purpose of a chemical termite soil barrier is to provide a continuous, no gap barrier between the building and the termite colony. It is therefore essential that the pest control operator is familiar with the construction details of the building. For further details, refer to the "Horizontal Barrier Treatments" and "Vertical Barrier Treatments" statements in this LEAFLET and to the Australian Standard AS 3660 Series.

Horizontal Barrier Treatments:

Use 5 L of solution per m^2 of soil. Apply the termitecidal solution evenly to the soil surface area to ensure the provision of a continuous barrier with no gaps. To minimise drift, use low pressure, high volume spray equipment delivering large coarse droplets. On impervious soils where the application of 5 L/ m^2 would cause excessive run-off, the application volume may be reduced provided the concentration of the solution is increased by a corresponding amount. For example, the volume of applied concentrate must remain constant at 25, 50 or 75 mL/ m^2 depending on the location and the situation. DO NOT apply solution volumes below 2 L/ m^2 . In situations where the soil surface is very dry and conditions are conducive to rapid drying, the areas to be treated should be moistened prior to the termitecidal application. It is important to note that when applying a horizontal barrier to the perimeter of a building or structure the chemical barrier is deemed to have a depth of 80 mm. In situations where the solution will not readily wet the soil to the required depth, loosen soil to a depth of 80 mm by 150 mm wide and apply 1.5 L of solution per lineal metre.

Vertical Barrier Treatments:

To install vertical barrier use a minimum of 100 L of solution per m³ of soil. Vertical barriers must be a minimum of 150 mm wide, extend down to 80mm below the top of the footing and be complete and continuous. Vertical barriers can be installed by trenching and treating the soil as it is backfilled, by soil rodding or by the use of certified reticulation systems, as described in the Australian Standard AS 3660 Series. The preferred method of installing a vertical barrier treatment is either by trenching and treating the soil as it is backfilled or by delivery via a certified reticulation system. When using the soil rodding method to establish a vertical barrier the distance between rod spacing should be as per the following table. To improve soil penetration, the soil should be loosened to depth of 150mm.

Soil type	Rod Spacing (mm)
Heavy clay	150
Clay loams	200
Loams	250
Sands	300

Perimeter Barrier Treatments:

Perimeter barrier consists of horizontal barrier at least 150mm wide adjoining a vertical barrier of at least 150mm in width. A perimeter barrier must completely surround all buildings, pipes, piers and service penetrations. In buildings with suspended floors with greater than 400 mm crawl space, perimeter barriers should be installed to surround piers, stumps and service penetrations and completely abut all substructure walls. To ensure provision of a continuous barrier use a minimum of 100 L of solution per m³ of soil. This equates to a delivery volume of 5 L of solution per linear metre for a 300 mm vertical barrier, or 10 L of solution per linear meter for a 600mm vertical barrier. Termites may gain access behind engaged piers against single brick walls unless the soil is treated on both sides of the wall down to the footing.

Post-Construction under Slab Treatments:

For concrete slabs, the solution needs to be injected through pre-drilled holes through the slab, at intervals between 150 mm and 300 mm. The following table shows the recommended hole spacing and recommended volume of spray solution required per hole, depending the soil type.

Soil type	Rod Spacing (mm)	Litres per hole
Heavy clay	150	1.5
Clay loams	200	2
Loams	250	2.5
Sands	300	3

Application equipment used to inject BIFORCE® 100SC WATER-BASED TERMITICDE & INSECTICDE through pre-drilled holes in an interior situation must be in good working order, free of any leaks and the injector must have tip shut-off to prevent nozzle dripping. Lateral dispersion tips are recommended. Drill holes must be resealed following injection of the BIFORCE® 100SC WATER-BASED TERMITICIDE & INSECTICIDE solution. The decision and/or need for drilling concrete floor slabs should only be made after thorough inspection of the building. The degree of termite activity should also be taken into consideration.

Treatment in Conjunction with Physical Barriers:

In situations where the termite protection system is to consist of a combination of both physical and chemical barriers, each certified system must be installed according to the relevant and appropriate product specification and the Australian Standard AS 3660 Series.

Reticulation systems:

BIFORCE® 100SC WATER-BASED TERMITICDE & INSECTICDE can be used through reticulation systems to form horizontal and vertical barriers under and around structures and all service penetrations. The reticulation system must be certified and be capable of distributing the termiticide solution according to the product label and Australian Standard AS 3660 Series. In situations using reticulations system to form barriers around perimeter and /or service penetrations only, a full pre-construction soil applied BIFORCE® 100SC WATER-BASED TERMITICDE & INSECTICDE horizontal barrier is recommended. It is the responsibility of the builder and all relevant sub-contractors to ensure that all termite barrier systems are installed in accordance with the relevant product installation directions and the Australian Standard AS 3660 Series.

Service Requirements:

Service requirements are to be determined as a result of least an annual inspection by a licensed Pest Control Operator. More frequent inspections may be required in high risk termite areas. In determining the need for service, factors such as local termite pressure, breaches of the barrier and termiteicide longevity should be considered.

Subterranean termites are on occasions capable of bridging termite barriers and therefore regular inspections, as detailed in the Australian Standard AS 4349.3 will significantly increase the probability of detection of termite activity before any damage or costly repairs are required.

Several factors contribute longevity of the termite treatment and must be considered when evaluating the need for re-treatment. The actual protection period will depend on the termite hazard, climate, soil conditions and rate of termiteicide used. Refer to Table A for the expected protection periods provided.

PRECAUTIONS AND RE-ENTRY PERIOD

DO NOT spray into the air or directly on humans, pets or animals. Avoid contact with food, food utensils or preparation surfaces.

Re-entry period

Pre-construction: Re-entry - **DO NOT** allow entry into uncovered treated areas until the spray has dried. When prior entry is necessary, wear cotton overalls buttoned to the neck, wrist and elbow-length PVC, neoprene or nitrile gloves and chemical resistant footwear. Clothing must be laundered after each day's use.

Post-Construction and urban pest control: Re-entry **DO NOT** allow people and pets to enter treated areas until the spray has dried. When prior entry is necessary, wear cotton overalls buttoned to the neck, wrist and elbow-length PVC, neoprene or nitrile gloves and chemical resistant footwear. Clothing must be laundered after each day's use.

PROTECTION OF WILDLIFE, FISH, CRUSTACEANS AND THE ENVIRONMENT

Dangerous to fish and aquatic organisms. DO NOT contaminate dams, rivers, streams or waterways or drains with product or used containers.

PROTECTION OF PETS AND LIVESTOCK

Before spraying, remove animals and pets from the areas to be treated. Cover or remove any open food and water containers. Cover or remove fish ponds, aquariums etc before spraying.

STORAGE, STORAGE AND DISPOSAL

Store in closed original container, in a cool, well-ventilated area away from children, animals, food and feedstuffs. DO NOT store for prolonged periods in direct sunlight. In case of spillage, confine and absorb spilled product with absorbent material such as sand, clay or cat litter. Dispose of waste as indicated below or according to the Australian Standard AS 2507 – Storage and Handling of Pesticides. DO NOT allow spilled product to enter sewers, drains, creeks or any other waterways.

For REUSABLE containers: Empty contents fully into application equipment. Close all valves and return to point of supply for refill or storage.

For 1 L, 5 L, 10L, 20 L containers: Triple or preferably pressure rinse containers before disposal. Add rinsing to spray tank. DO NOT dispose of undiluted chemicals on-site. If recycling, replace cap and return clean containers to recycler or designated collection point. If not recycling break crush or puncture and bury empty containers in a local authority landfill. If no landfill is available, bury the containers below 500 mm in a disposal pit specifically marked and set up for this purpose clear of waterways, vegetation and tree roots. Empty containers and product should not be burnt. DO NOT bury waste or surplus product. Dispose of undiluted waste by either dilution and use according to the Directions for Use or returning to the point of purchase in the original container for controlled disposal. Dispose of diluted surplus product by using according to the Directions for Use. DO NOT re-use empty container.

Envirodrum Micro Matic valve (200L)

Store the original sealed Envirodrum in cool well-ventilated areas. DO NOT store for prolonged periods in direct sunlight. DO NOT tamper with Micro Matic valve or the security seal. DO NOT contaminate the Envirodrum with water or any foreign matter. After each use of the product, please ensure that the Micro Matic coupler delivery system and hoses are disconnected, triple rinsed with clean water and drained accordingly. When the contents of the Envirodrum have been used, please return the Envirodrum to the point of purchase. The Envirodrum remains the property of Sherwood Chemicals.

SAFETY DIRECTI ONS

Poisonous if swallowed. Will damage the eyes and will irritate the skin areas. Avoid contact with eyes and skin. DO NOT inhale vapour or spray. When opening the container and preparing spray, wear cotton, overalls buttoned to the neck and wrist, a washable hat, elbow-length PVC, neoprene or nitrile gloves, face shield or goggles and chemical resistant footwear. When using prepared spray, wear cotton overalls buttoned to the neck and wrist, a washable hat, elbow-length PVC, neoprene or nitrile gloves and chemical resistant footwear. When using in enclosed areas wear cotton overalls buttoned to the neck and wrist, a washable hat, elbow-length PVC, neoprene or nitrile gloves, and chemical resistant footwear and half-face respirator with the combined dust and gas cartridge. If clothing becomes contaminated with product or wet with spray, remove clothing immediately. If product or spray on skin, immediately wash area with soap and water. If products in eyes wash it out immediately with water. Thoroughly ventilate treated areas before reoccupying. After use and before eating, drinking, or smoking, wash hands, arms and face thoroughly with soap and water. After each day's use, wash gloves, face shield or goggles, respirator (if rubbers wash with detergent and warm water) and contaminated clothing.

FIRST AID

If poisoning occurs, contact a doctor or Poisons Information Centre. Phone Australia 13 11 26. See additional information on the **Material Safety Data Sheet**.

MATERIAL SAFETY DATA SHEET

Additional information is listed in the Material Safety Data Sheet (MSDS). A MSDS for BIFORCE® 100SC WATER-BASED TERMITICIDE & INSECTICIDE is available from Sherwood Chemicals on request. Call customer service on Tel: 0421 667 972

CONDITIONS SALE: The use of BIFORCE® 100SC WATER-BASED TERMITICIDE & INSECTICIDE being beyond the control of the manufacturer, no warranty expressed or implied is given by Sherwood Chemicals regarding its suitability, fitness or efficiency for any purpose for which it is used by the buyer, whether in accordance with the directions or not. Sherwood Chemicals accept no responsibility for any consequence whatsoever resulting from the use of this product.

APVMA Approval No. 62837/ 0409